UNITED NATIONS

ECONOMIC AND SOCIAL COUNCIL

Eighth United Nations Regional Cartographic Conference for the Americas New York, 27 June1 July 2005 Item 5 of the provisional agenda*

COUNTRY REPORTS

Cartographic Work in Japan 2000 - 2005

Submitted by (Japan)*

* E/CONF.96/1

Cartographic Work in Japan 2000 – 2005

Government of Japan

Summary

In Japan, fundamental geodetic work is carried out principally by the Geographical Survey Institute (GS) and the Hydrographic and Oceanographic Department (HOD) of the Ministry of Land, Infrastructure and Transport (MLIT). Various map preparation is conducted by GSI, HOD, the Ministry of Agriculture, Forestry and Fisheries (MAFF), and the Geological Survey of Japan/ National Institute of Advanced Industrial Science and Technology (GSJ/AIST). It should be noted that the National Land Agency (NLA) was integrated into MLIT due to the governmental restructuring in 2001.

Various geodetic survey activities are being carried out, such as:

Operation of a nationwide GPS observation network for precise geodetic control surveying and crustal movement monitoring; detection of crustal movement for earthquake prediction research; leveling in the ground subsidence areas; geodetic satellite observation for control of the geodetic networks and for determination of positions of isolated islands; geoid surveys for the determination of geoid height; gravity measurement for preparation of gravity anomaly charts; geomagnetic observation for preparation of geomagnetic charts.

In addition, global geodetic projects which connect the Japanese geodetic network to the world geodetic system are being undertaken by GSI; utilizing VLBI (Very Long Baseline Interferometry) system, and by HOD; utilizing SLR (Satellite Laser Ranging) system, respectively.

GSI has been periodically revising national base maps at the scale of 1:25,000, preparation of basic maps at the scales of from 1:5,000 to 1:5,000,000, and several kinds of thematic maps such a s land use maps, land condition maps, etc.

In 1995, GSI started the preparation of the Spatial Data Framework (SDF) at the scale level of 1:2,500 for urban areas and that of 1:25,000 for the rest of the country. GSI completed the preparation of SDF by 2003, and publishes the data in CD-ROM.

MLIT (NLA) has been conducting cadastral survey. The scales of cadastral maps are from 1:250 to 1:5,000. MLIT (NLA) has also been producing land classification maps on the scales of from 1:5,000 to 1:200,000 and water use maps on the scales of 1:25,000 and 1:50,000.

MAFF has been producing soil maps of cultivated and forest lands and has already covered all the national forests in a series of soil maps.

GSJ/AIST has been producing geological, geophysical, geochemical and other thematic maps on the scales of from 1:50,000 to 1:5,000,000.

To promote safe navigation, HOD has been publishing various nautical, bathymetric and tidal current charts, including electronic navigational charts (ENC) in CD-ROMs.

Cartographic Work in Japan 2000-2005

Most of the cartographic work in Japan is carried out under the Survey Act. Main objectives of the act are to coordinate various survey work efficiently, to standardize accuracy and to avoid duplicated work.

Survey work is mainly classified into two categories by the act. The first one is the Fundamental Survey executed nationwide by the Geographical Survey Institute (GSI), and the other is the Public Survey for local governmental projects or special projects which are carried out by other governmental or public organizations such as the Forestry Agency, the Geological Survey of Japan/ National Institute of Advanced Industrial Science and Technology (GSJ/AIST), the Ministry of Land, Infrastructure and Transport (MLIT), etc.

Preparation of various kinds of charts and nautical publications is carried out by the Hydrographic and Oceanographic Department (HOD) of the Japan Coast Guard.

1. Geodetic Work

Fundamental geodetic works in Japan are principally executed by the Geographical Survey Institute (GSI) and the Hydrographic and Oceanographic Department (HOD).

The Japanese national geodetic network consists of 1,000 first order triangulation points, 5,000 second order triangulation points, 32,700 third order triangulation points and 64,500 fourth order triangulation points, and 20,000 km of precise leveling routes. Fourth order triangulation points are still being added mainly for cadastral surveys.

The establishment of a nationwide GPS observation network has started in 1992, and the operation started in 1994.

The Survey Act was amended and put into force as of 1 April 2002, by which the Japanese Geodetic Datum 2000 (JGD2000), a world geodetic system, was adopted as the national geodetic datum for surveying and mapping in place of the Tokyo Datum.

The Law for Hydrographic Activities was amended and put into force as of 1 April 2002, the Japanese domestic positional reference frame was changed from the Tokyo Datum (TD) to the World Geodetic System (WGS). Accordingly, datum of Japanese nautical charts and those in the Notices to Mariners and the Navigational Warnings have been integrated into the WGS.

1.1 Precise Geodetic Network Surveying Project

GSI started the Precise Geodetic Network Surveying Projects in 1974 in order to switch over from old geodetic data obtained by conventional method (such as triangulation) to more precise new data by trilateration, using optical EDMs (Electro-optical Distance Measuring instruments). Since1990, Surveying the first and second order triangulation points with optical EDM has been replaced by surveying with GPS. The geodetic framework of the project was classified into two networks. One was the Primary Precise Geodetic Network composed of 6,000 first and second order triangulation points, and the other was the Secondary Precise Geodetic Network composed of 32,700 third order triangulation points. GSI put an end to the project in 2003 and started a new project in 2004 to maintain the geodetic framework re-established based on JGD2000. The work of maintenances consists of two components: the continuous observations of the nationwide 1229 GPS stations and the periodic surveys of 2400 triangulation points evenly distributed over the country. The latter is named Densitied Precise Geodetic Network using GPS.

Recently major technique used for this survey was changed from EDM to GPS (Global Positioning System). GSI started the operation of the nationwide GPS observation network composed of 210 GPS observation stations called 'GPS-based Control Stations' in 1994. Additionally, 1019 GPS-based Control Stations had been added by March 2005. The network is operated continuously and the data are transferred to GSI in real time.

1.2 Leveling

GSI accomplished the eighth revision leveling survey along the first order leveling routes throughout Japan in March 1997. The ninth revision leveling survey has been carrying out from April 1997. About 2,000 km of revision surveys are carried out every year. In addition to the revision survey, GSI is conducting 2,000 km of re-leveling annually in the Specified Observation Areas and the Intensified Observation Areas designated in the National Earthquake Prediction Program.

153 tidal stations are registered with the Coastal Movement Data Center and all the tidal

data obtained at these stations are compiled and published every year.

1.3 Satellite Positioning

GPS observation is a large part of satellite positioning of GSI. Continuous observation at 1229 GPS-based control stations plays a main role in crustal deformation monitoring in GSI. A sides from continuous observations, GPS is used for positioning of control surveys in Japan.

GSI is also carrying out data submission to IGS (International GNSS service), IGS data distribution as a Operational Data Center and IGS data analysis as a Regional Network Associated Analysis Center.

GSI has been carrying out EGS (Experimental Geodetic Satellite, nicknamed "AJISAI") observation since 1986. Observation of EGS are carried out also by JAXA (Japan Aerospace Exploration Agency) and HOD. GSI is carrying out spin rate estimation by photoelectric observation.

In order to measure the precise position of the mainland and islands of Japan in the World Geodetic System, HOD has been conducting a satellite laser ranging (SLR) observation of LAGEOS at the Shimosato Hydrographic Observatory since 1982, and has constantly determined the positions of more than 70 off-lying islands using differential techniques of NNSS since 1974 and GPS since 1994.

HOD started a marine geodetic control project in 1988 to determine the precise position of 10 major islands of Japan by the simultaneous SLR observation of AJISAI, and has already determined the precise position of 9 islands (all islands but Etrofu Shima). HOD studied the plate movement around Japan Islands by repeated observations of our geodetic control points which include Chichi Shima, Ishigaki Shima, Tsushima, and Wakkanai. The observations were performed at Wakkanai in 2000, and Tsushima in 2001.

Both of these SLR observations are supported by the cooperative research provided by the U.S.A-Japan cooperation in the field of space development.

In order to watch the middle size crustal deformation (about 50km), HOD continuously monitors the baselines in the Minami Kanto area, known as the nest of big earthquakes, by GPS geodetic survey in Izu Oshima, Manazuru, Yokosuka, Minami Izu, Kozu Shima, Miyake Shima and Hachijyo Shima.

HOD has been conducting GPS geodetic survey to detect the crustal deformation at the Japanese coastal area.

1.4 Astronomical Observation

HOD is also carrying out the observation. For the purpose of preparing the Japanese Ephemeris (the most precise almanac in Japan), nautical almanac, abridged nautical almanac, etc., HOD has been conducting observation of occultation of stars by the moon at the hydrographic observatories at Tokyo, Sirahama, Simosato and Bisei, and grazing occultation at two places in Japan.

1.5 Very Long Baseline Interferometry (VLBI)

GSI has been operating four permanent stations at Shintotsukawa with 3.8m, at Aira with 10m, at Chichijima with 10m, and at Tsukuba with 32m diameter antenna. GSI has carried out domestic VLBI experiments with four stations monthly. Tsukuba has been participating in international VLBI projects of VLBI global network for a deeper understanding of inter/intra-plate crustal deformation and Earth orientation changes. The projects are Continuous Observation of the Rotation of Earth(IVS-R), The International Terrestrial Reference Frame sessions(IVS-T), The Astronemical geodesy sessions(VLBA),The monitor UT1 sessions(IVS-INT2), and Asis-Pacific Space Geodynamics(APSG). The major purposes of GSI's VLBI activities are below.

a) Connecting Japanese geodetic reference frame referred to International Terrestrial Reference Frame(ITRF) to participate in the International VLBI Service(IVS).

b) Precisely finding the movement of continents or the variability of the earth rotation to carry out VLBI experiments repeatedly.

c) The monitoring of mean sea level change to measure the position of tidal stations by VLBI and GPS repeatedly.

d) Establishment of a terrestrial reference frame is Asia and the pacific area by geodetic survey techniques in cooperation with the related countries.

1.6 Gravity Survey

Gravity Surveys are executed on land by GSI and at sea by HOD. GSI is repeating fundamental and 1st order gravity surveys at fundamental and 1st order gravity stations to detect gravity changes associated with crustal movements. Since 1984, an absolute gravity measuring system has been operated for fundamental gravity survey. Since 1992, GSI has introduced FG-5 absolute gravimeters and measured absolute gravity at the fundamental gravity stations. GSI and other organizations that own FG-5 absolute gravimeters in Japan, have been conducting intercomparison of FG-5 in order to detect the instrumental differences. Intercomparison has been started in 2002, and held for 6 times so far..

In 2001 and 2004, GSI conducted the forth absolute gravity measurement at Syowa Station as an activity of the 42nd and 45th Japanese Antarctica Research Expedition (JARE).

In March 2000, GSI produced gravity anomaly relief maps of Japan in collaboration with Nagoya University, the Geological Survey of Japan (GSJ/AIST), and Hokkaido University.

In April 2002, GSI published a new 2km-grid geoid model of Japan "GSIGEO2000". GSIGEO2000 is a hybrid geoid model constructed by adopting the gravimetric geoid model "JGEOID2000" to the nationwide geoidal heights data of more than 800 points by GPS/leveling (that is, GPS survey at benchmarks).

HOD has been conducting gravity measurements in the Izu Syoto every year. These observation data are used to delineate vertical crustal movements related with earthquakes and volcanic eruptions.

HOD has also been conducting the gravity surveys at sea area using survey vessels for prediction of earthquake and volcanic eruptions.

GSJ/AIST has conducted gravity surveys for the coverage of regions scarce of data, a part of Kyushu, Chugoku and Shikoku districts, southwestern Japan, during the period from 1999 to 2003. The results are being published as "Gravity maps (Bouguer Anomalies) at 1:200,000 scale", and 22 maps of this series have been published as of April 2005. GSJ/AIST also compiled "Gravity Map of Japan (Bouguer Anomalies)" using total of about 350,000 land data and about 1,000,000 marine data in 1999. The Japanese Islands and their adjacent sea areas are covered by these sheets of the map at 1:1,000,000 scale. The digital data for the map was published in 2000 with CD-ROM. GSJ/AIST has been conducted marine gravity surveys since 1974 as a part of the geological mapping program of continental margin around the Japanese Islands. The survey vessel Hakurei-maru No.2 has been used since 2000 after the retirement of the 26-years-old Hakurei-maru. The cruises until 2002 have covered almost the continental margin around the Japanese Islands. Free-air and Bouguer anomaly maps have been published as appendices of "Marine Geology Map Series" at a scale of 1:200,000. 1:1,000,000 scale.

1.7 Geomagnetic Survey

GSI has been conducting land geomagnetic and aeromagnetic surveys. The land geomagnetic surveys are conducted at 105 1st order geomagnetic stations at about two or five year intervals. GSI also set up 11 continuous observation stations of geomagnetism throughout Japan for continuous geomagnetic observation and has started observation since 1996. Geomagnetic continuous observation has also been carried out in the Kanozan, Mizusawa and Esashi observatories.

The data obtained by GSI are used for compilation of magnetic charts on the scale of 1:4,000,000 for D (declination), H (horizontal intensity), I (inclination), Z (vertical intensity) and F (total intensity) components. In April 2002, GSI published the magnetic charts for the epoch of 2000.0.

GSI completed a nationwide aeromagnetic survey at an altitude of 5000m on 1999. The data was compiled to publish the aeromagnetic total intensity chart at 5000m for the epoch of 1995.0.

GSI carried out a precise aeromagnetic survey at Mt. Usu and Mt.Tarumae areas in 2000, Mt. Komagatake in 2001 and Mt. Bandai in 2002. The results of the precise aeromagnetic survey at Mt. Iwate in 1999 and Mt. Usu in 2000 was compiled to aeromagnetic anomaly charts, and published in 2000 and 2001 respectively.

HOD conducted landmagnetic and aeromagnetic surveys on and over the Japanese islands and its surrounding waters. In order to maintain the safety of a vessel or an aircraft using a magnetic compass, magnetic variations and annual changes must be shown on the nautical and aeronautical charts. For that, HOD is re gularly conducting geomagnetic observations and measures

magnetism and annual variations by means of land magnetic surveys at the repeated observation points every five years.

HOD has been conducting the magnetic surveys at sea area using survey vessels for prediction of earthquake and volcanic eruptions. HOD carries out the land and aeromagnetic surveys to predict volcano eruptions.

GSJ/AIST has been conducting high-resolution aeromagnetic surveys over the Japanese islands and adjoining sea areas, using an airborne magnetometer of Cesium optical pumping type or proton precession type with high repetition rate. Total intensities (F) of magnetic field in the air are observed along with the precise position-fix data acquisition. Data obtained are processed and magnetic anomaly field is extracted after removing the International Geomagnetic Reference Field (IGRF), which are published as aeromagnetic anomaly maps at the scale of 1:25,000 to 1:200,000.

Recent target areas of high-resolution aeromagnetic survey are mostly related to the elucidation of active volcanoes. In 2000, a helicopter borne survey employing a nose-stinger system was conducted over Usu volcano with a special reference to the 2000 eruption, revealing the precise image of subsurface structure of the volcano.

"High –resolution aeromagnetic map of Usu volcano" a scale of 1:25,000 published in 2003 is one newest of the aeromagnetic map series. Similar surveys but with magnetic and EM bird systems were also conducted over Usu and Iwate volcanoes to monitor the course of those volcanic activities. A new helicopter borne survey system has been developed recently at GSJ/AIST especially for the survey over rugged mountains even higher than 3,000m ASL.

1.8 Synthetic Aperture Radar Interferometry

In order to obtain high resolution surface displacement over a large area, GSI studies synthetic aperture radar (SAR) interferometry. One of its achievements is the detection of surface displacement with JERS-1 (Japanese Earth Resources Satellite-1) SAR data. GSI has been preparing for the next L-band SAR satellite ALOS (advanced Land Observing Satellite) data analysis system.

1.9 Precise distance measurements

GSI has carried out precise distance measurements using precise short-range EDM (ME-5000) with resolution of 0.5 mm for the purpose of observing crustal movements in swarm earthquakes area and active faults.

1.10 Mobile Observation

GSI has carried out observation of crustal movements in Mt. Usu and Miyake volcanic area with a mobile GPS continuous station and an automated polar system (APS) since 2000, when the volcanic activities of Mt. Usu and Miyake started.

1.11 Unmanned/manned Survey Launches

JCG has two unmanned/manned survey launches, "JINBEI" and nicknamed "MANBO?", to investigate submarine volcances. "JINBEI" was launched in 2002. "MANBO?" was constructed as a survey launch of survey vessel "SHOYO" in 1998. They can be operated in unmanned remote-controlled mode in the dangerous area. "MANBO?" surveyed a submarine volcances off Miyakejima Island in 2002, "Minami-Hiyoshi Seamount" in 2002 and Kita-Fukutoku-tai in 2003 for the volcanic eruptions prediction.

1.12 The Earthquake Prediction Program

GSI has been participating in the National Earthquake Prediction Program. In order to monitor the crustal activity in and around the Japanese islands, GSI has been conducting several kinds of geodetic surveys and researches on measurement techniques and crustal movements. Detected crustal movements have been compiled and reported to the Coordinating Committee for Earthquake Prediction (CCEP), the Earthquake Assessment Committee and the Earthquake Research Committee.

GSI has been conducting the Precise Geodetic Network Survey and leveling to reveal horizontal and vertical crustal movements, respectively. The results have contributed to the long-term prediction of earthquakes as the designation of the Intensified Observation and Specified Observation Areas. GSI has carried out distance measurements and leveling in the regions which

suffered from severe damages of earthquakes. In 2000, GSI revealed crustal movements associated with the Tottori-ken-seibu earthquake.

GSI has also been conducting precise distance measurements and leveling with a short interval and continuous GPS observations in the Intensified Observation and Specified Observation Areas for the purpose of short-term prediction. Furthermore GSI has been continuously monitoring crustal tilts and strains in the Intensified Observation Areas with extensometers and long baseline tiltmeters. In particular GSI detected crustal movements associated with the eruption of Usu and Miyake-jima volcano and the Tokai silent earthquake.

The CCEP was established in 1969 to exchange information on crustal activities and evaluate them. The CCEP consists of 30 members from agencies and universities conducting observations and researches for earthquake prediction. GSI has been serving as the secretariat of the CCEP since its establishment.

HOD surveys for the earthquake prediction program. In order to obtain data and information necessary for the prediction of earthquakes, magnetic and gravity surveys were conducted in specific areas off Miyagi. Total intensity magnetic anomaly and free-air gravity anomaly maps were made for elucidation of sea-bottom structure. Free-air gravity anomaiy is also used to calculate precise geoid.

For this purpose, magnetic and gravity surveys were also conducted in offing Miyagi and other plate boundaries. Total intensity magnetic anomaly and free air gravity anomaly maps were made for elucidation of sea-bottom structure. Free air gravity anomaly is also used to calculate precise geoid.

The seafloor geodetic observation using a combined technique of the kinematic GPS and acoustic ranging has started in 2000 off Sanriku coast. Until 2004, HOD has been establishing 18 seafloor geodetic reference points mainly on the land-ward slope of the major trenches, such as Japan Trench and Nankai Trough, and started repeated observations. The primary purpose is to detect and monitor the seafloor crustal movement affected by the subduction of oceanic plates.

1.13 Japanese Geodetic Datum 2000 (JGD2000)

As of April 2002, the century old Tokyo Datum has been legally superseded by a brand new one, the Japanese Geodetic Datum 2000 (JGD2000), which is a local definition of International Terrestrial Reference System (ITRS) at the epoch of 1997.0 with a reference ellipsoid of GRS80 mainly based on space geodetic techniques such as GPS and VLBI. Tokyo Datum had the origin shift of -146m, 507m, 681m in XYZ components with respect to ITRS, and the old geodetic network suffered from internal distortions due to accumulation of crustal deformations and inevitable survey errors. Now GSI provides newly adjusted coordinates of GPS continuous observation stations (1,200 pts) and he 1st to 3rd order horizontal control points (about 38,000 pts), together with transformed coordinates of the 4th order control points (about 64,000 pts). Orthometric heights of benchmarks (about 20,000 pts) adjusted in 2000 and geoidal heights computed from the hybrid geoid model GSIGEO2000 based on gravimetric and GPS / leveling data complete a new geodetic reference system of Japan.

		2000	2001	2002	2003	2004	Total
Primary Precise Geodetic Network		108	104	95	101		408
using GPS							
Secondary P	recise Geodetic	197	200	104	102		603
Network using GPS							
Densitied pro	ecise Geodetic					199	199
Network using GPS							
Fourth Order Triangulation		1,018	1,109	1,166	1,232	1,181	5,706
First Order Revision Leveling		3,877	3,593	4,107	4,964	3,924	20,465 km
Satellite Laser	Mainland	Since		1982			1
Ranging(HOD)	Islands	1	1	0	0	0	2
GPS	GPS-based	GSI		253	24	5	1,229
	Control Stations						
	Islands	HOD	10	12	6	6	44
		10					

Table 1. Geodetic Work for the Period from 2000-2004

VLBI	Stations	5	5	5	4	4	23
Geoid observation	on (GPS/Leveling)	-	186	111	104	129	530
Gravity Survey	Fundamental	5	6	4	4	5	24
	(GSI)						
	1 st Order (GSI)	8	39	35	20	37	139
	2 nd Order (GSI)	34	-	-	126		160
	Island/Harbors	1	3	2	1	0	7
	(HOD)						
	Sea (HOD)	3	3	2	4	1	13
	Others (GSI)	1(Antar	-	-	1(Anta r		2
		ctica)			ctica)		
Geomagnetic	Fundamental						11
Survey	Magnetic						
	Stations (GSI)						
	1 st Order (GSI)	9	7	6	11	15	48
	Island (HOD)	0	2	1	1	0	4
	Sea (HOD)	2	3	2	3	1	11
Aeromagnetic	Volcanic area	2 areas	1 area	1 area			4 areas
Survey	(GSI)						
	Land/Sea (HOD)	2,400	1,200	1,400	1,100	2,100	8,200km

*In all tables in this report, year represents Japanese fiscal year which starts from April of the year and ends in March of the next year. (Except Notices to Mariners, Japan Navigational Warnings, NAVAREA XI navigational warnings and NAVTEX navigational warnings in Table 14) *Numbers in the table mean the number of surveyed points unless otherwise specified.

2. Topographic Mapping

2.1 Medium Scale Topographic Maps

The first national base map series covering the entire country of Japan was 1:50,000 Topographic Maps, whose preparation began in 1895 and was completed in 1925 by GSI.

In 1964, GSI adopted 1:25,000-scale Topographic Maps as the national base map replacing 1:50,000-scale maps. The preparation of 1:25,000-scale Topographic Maps was pushed forward over the whole country of Japan and was for the most part completed by 1983.

GSI has been revising these maps in accordance with the following principles:

- The 1:25,000-scale Topographic Maps are revised every three years for urban areas, five years for suburban areas and ten years for mountainous areas. Regardless of this principle, maps are revised when significant features like new highways are constructed.
- The 1:50,000-scale maps are revised subsequent to the revision of the corresponding 1:25,000-scale Topographic Maps.

In 1974, GSI started the Digital National Land Information project in cooperation with the National Land Agency (NLA). Various categories of information, such as elevation, coast lines, rivers, roads, railways, administrative boundaries, land use, etc., have been collected from 1:25,000, 1:50,000 and other smaller scale map sheets and filed into magnetic tapes for each category.

In 1984, GSI started a new digital map information project and began to collect the data for basic features of 1:25,000-scale Topographic Maps, namely, contour lines, administrative boundaries, roads, railways and shorelines. The purpose of this project was to prepare a digital cartographic database for automated compilation and production, and to provide basic data for GIS and other digital data services. Out of these features, GSI published digital elevation model (DEM) data derived from contour lines, administrative boundaries, shorelines, geographical names and public facilities in CD-ROMs.

In 1993, GSI adopted the raster-based revision method for the 1:25,000-scale Topographic Maps, replacing the conventional method. GSI digitized 1:25,000 or 1:50,000-scale Topographic Maps in raster format to adopt this method and released them in CD-ROMs.

In order to facilitate the revision of 1:25,000-scale Topographic Maps, GSI started digitizing the maps in vector format and completed the project in 2001. The ten basic features (roads,

railways, rivers, waters, coastlines, administrative boundaries, datum points, geographical names, public facilities and elevation) of the resulting vector database were published in CD-ROMs as part of SDF.

Taking advantage of the vector database, GSI developed and implemented New Topographic map Information System (NTIS), a vector-based map revision system in 2001. This system also transforms the datum of the database from the old Tokyo datum to the new JGD2000. NTIS has the following five design concepts:

- Elimination of dual management of data
- Introduction of time series management of each vector object
- Realization of a seamless database for all Japan
- Adoption of implicit topology data structure
- Separation between data model and map drawing method

GSI now collects change information for map revision from local governments and public corporations through its ten regional branches to achieve near real-time map database revision for Topographic Maps.

GSI is also developing software to revise 1:50,000 Topographic Maps using NTIS database.

2.2 Large Scale Topographic Maps

GSI initiated the National Large Scale Topographic Mapping Project in 1960, in order to map the populated areas of the country. The Forestry Agency also began promoting a similar project in mountainous areas, for the purpose of producing a Basic Forest Map (BFM) as the basis for surveying forests. The project covering mountainous areas was completed in 1980.Currently the Forestry Agency is promoting revision work of the existing Basic Forest Map.

Until 1974, local governments had been producing large scale urban planning base maps with their own standards. In 1975, GSI and the City and Regional Development Bureau of the Ministry of Land Infrastructure and Transport (MLIT) standardized the 1:2,500 urban planning mapping process by promoting the 1:2,500 scale map joint mapping projects with GSI. In the projects, GSI took aerial photographs and conducted aerial triangulation while local governments undertook the mapping process such as stereo plotting, map compilation and printing. Approximately 50,000km² out of the urban planning areas were mapped in accordance with the standards by the end of 1996. These maps are supposed to be revised every five years by the local governments.

GSI has been collecting and publishing Detailed Digital Information (10m Grid Land Use) since 1981 under the project of the Survey on the Trend of Housing Land Use, the objective of which is to prepare detailed information on present housing lots and possible future housing lots in the urban areas of Tokyo, Osaka and Nagoya.

In 1983, GSI began to compile 1:10,000-scale Topographic Maps for urban areas by compiling existing 1:2,500 scale maps and publish them.

In 1988, GSI proposed standards for large scale mapping with digital processes. Since then, most of local governments that have urban planning areas have mapped most large scale maps in accordance with the standards.

In Japan, digital map data have been produced and used for urban planning, utility management, navigation, etc. by public organizations and private companies. Under these circumstances, the effective and proper use of digital maps is indispensable. To avoid duplication of mapping and to maintain accuracy, GSI initiated the Kokudo-kihon-zu (Japanese phrase for "National Large Scale Map") Data Base (KDB) project in 1989. In this project, digital map data produced at the scales between 1:500 and 1:10,000 by fundamental and public surveys have been compiled and stored in KDB, which was opened to the public in 1993.

Since 1995 GSI has been producing SDF data at the scale level of 1:2,500 for GIS applications with items including road networks, administrative boundaries and inland water areas, and published them in CD-ROMs. The development of 1:2,500-level SDF was completed by 2002 for approximately 96,000km² of urban areas that are designated as urban planning area.

In 2003, using technology of aviation laser scanner surveying, GSI started publication of very detailed and highly precise DEM (digital elevation model), which grid interval was 5-meter.

Table 2 shows the coverage of large and medium scale topographic maps prepared by GSI during the past five years.

Table 2. Coverage of Large and Medium Scale Topographic Maps by GSI

	Title	Fy2000	Fy2001	Fy2002	Fy2003	Fy2004
1:10,000	New edition	-	23 sheets	27	83	2
				sheets	sheets	sheets
	Revision	59 sheets	60 sheets	43	26	25
				sheets	sheets	sheets
1:25,000	Revision	878 sheets	1,299	42,989 km ²	170,166	372,863
			sheets		km ²	km ²
1:50,000	Revision	84 sheets	119 sheets	127 sheets	58	-
					sheets	
	Recompilation	1 sheet	-	1 sheet	-	8 sheets (trial)

Currently Forestry Agency is promoting Forest GIS (Geographic Information System) and digital mapping work of Forest Planning Maps. Table 3 shows the basic forest mapping work during the same period.

Table 3. Basic Forest Mapping

Title	2000	2001	2002	2003	2004
1:5,000 Photomaps	499km ²	731km ²	780km ²	859km ²	899km ²
1:5,000 BFM Revision	992km ²	1,156km ²	927km ²	2,428km ²	2,172km ²

2.3 Small Scale Maps

Small scale maps and others published by GSI are shown in Table 4 and Table 5 (April, 2005).

Table 4. Publication of Digital Maps

Title	Number of	Area
	CD-ROM	
DM 2500 (Spatial Data Framework)	16	Urban Planning Area
DM 25000 (Spatial Data Framework)	53	All Japan
DM 25000 (Map Image)	75	All Japan
DM 25000 (Administrative Boundaries)	1	All Japan
DM 25000 (Geo. Names, Pub. Facilities)	1	All Japan
DM 50000 (Map Image)	30	All Japan
DM 200000 (Map Image)	3	All Japan
DM 500000(Combined)	1	All Japan and Surroundings
DM 5m Grid (DEM)	3	Saitama, Tokyo, Nagoya
DM 10m Grid (DEM (Volcanic Areas))	1	13 Volcanic Areas
DM 50m Grid (DEM)	3	All Japan
DM 250m Grid (DEM)	1	All Japan
The National Atlas of Japan	1	All Japan

DM: Digital Map, DEM: Digital Elevation Model

Table 5. Publication of Paper Map Preparation

Title	Number of	Size of sheets	Number of	Remarks
	sheets		Colors	
1:10,000 Topographic Map	300	52.0 x 73.8 cm	5	
	4		10	
1:25,000 Topographic Map	4,344	46.0 x 58.0 cm	3	
	19	59.4 x 84.1 cm	6	
1:50,000 Topographic Map	1,291	46.0 x 58.0 cm	4	
	4	46.0 x 58.0 cm	6	
1:200,000 Regional Map	130	46.0 x 58.0 cm	6	Hill

				Shading
1:500,000 District Map	8	78.8 x 109.1 cm	7	Layer
	8	78.8 x 109.1 cm	4	Tints
1:1,000,000 Nippon	3	78.8 x 109.1 cm	9	Layer
				Tints,
				Hill
				Shading
1:3,000,000 Japan and Her	1	78.8 x 109.1 cm	12	Layer
Surroundings				Tints,
				Hill
				Shading
1:5,000,000 Japan and Her	1	78.8 x 109.1 cm	9	Layer
Surroundings				Tints
1:25,000 Composite Map	1	63.6 x 93.9 cm	14	
1:50,000 Composite Map	3	63.6 x 93.9 cm	14,16	
1:100,000 Composite Map	1	63.6 x 93.9 cm	4	
	5	78.8 x 109.1 cm	5, 16	
1:300,000 Composite Map	1	78.8 x 109.1 cm	6	Hill
· · ·				Shading

3. Metadata and Clearinghouse

In Japan, Japanese Metadata Profile (JMP) is used for registering a metadata with the clearinghouse. JMP1.1a was developed based on the 1st Committee Draft (CD) of ISO19115 under a joint research project between GSI and private companies. Central government adopted JMP1.1a for its metadata preparation. Then revising the JMP1.1a was frozen during CD and DIS stage in ISO/TC211. JMP2.0 has been developed on May 2003 based on ISO 19115 issued on March 2003. JMP2.0 is composed of core metadata and some elements such as keywords, distribution information and so on which are necessary for clearinghouse activities.

GSI has operated the Japanese clearinghouse gateway under the Japanese language environment since 2000. JMP is adopted as the Metadata form, and ISO 23950 as the retrieval protocol.

Now there are twenty one clearinghouse nodes.

- Thirteen nodes by seven central government ministries.
- Four nodes by private companies.
- Four nodes by research institutes including universities.

The node number of the central government is increasing under the Action Program. Regarding the basic surveys by local governments, Japan has a system of gathering the abstract information of public survey to avoid duplicate survey based on Survey Act. GSI is the organization responsible for gathering the abstract information of public survey. GSI can easily convert the abstract information into metadata. These metadata are registered and distributed through a public survey clearinghouse node. One special clearinghouse is by National Spatial Data Infrastructure Promoting Association (NSDIPA). Many private companies register metadata in the clearinghouse. It is a single node but covers many private companies. Through the clearinghouse gateway by GSI, the government metadata and private companies' metadata can be retrieved.

The URL of this clearinghouse gateway is http://zgate.gsi.go.jp/, in Japanese.

4. Thematic Mapping

4.1 Geographical Thematic Map

GSI is engaged in various kinds of thematic mapping in cooperation with other governmental organizations for the purpose of providing basic geographic information for regional development, disaster prevention, etc. Table 6 shows some typical thematic maps prepared and published by GSI during April 2000- March 2005.

GSI generates digital thematic maps by both digital mapping method and digitization from existing maps. Table 7 shows some typical Digital thematic maps prepared and published by GSI.

In 1999 GSI started to digitize thematic information of existing thematic maps in order to display and analyze with other information on GIS (Geographic Information System). Digitization of

the land condition maps and active fault maps in urban area are on going, and other thematic maps are planned to be digitized in due course.

Table 0. The matic Mapping by $GSI(2000 - 2003)$	Table 6.	Thematic I	Mapping	by GSI	(2000 - 2005)
--	----------	------------	---------	--------	---------------

Type of Map	Scale	Number of sheets
Basic volcano map	1: 5,000, 1:10,000	32
Land condition map	1:25,000	5
Land condition map of volcano	1:30,000, 50,000	3
Topographic map of costal areas	1:25,000	4
Land condition map of coastal areas	1:25,000	4
Lake chart	1:10,000	2
Active fault map in urban area	1:25,000	60

Table 7. Digital Thematic Mapping by GSI

Title	Format	Item or explanation	Original Source
Detailed Digital	10m grid	Land use for housing, covering the	City Planning Map,
Information		three main urban areas of Japan.	Aerial Color Photograph etc.
(1981-, GSI)			
Digital National	1km grid	Coastline, Topography, Land	Topographic Map,
Land Information	250m grid	Classification, Land Use, River	Thematic Map etc.
(1975-, GSI, NLA,	100m grid	Basin, Administrative Boundary,	
HOD, JMA)	point	Road, Railway, Public Facility, Land	
	line	Price etc.	
Digital Map 10m	10m Grid	Elevation	1:5000 and 1:10,000 scaled
Grid (Elevation of			Volcanic Base Maps
Active Volcanos)			
,			

4.2 Soil Maps

Soil maps in Japan are roughly divided into two categories; for cultivated lands and for forest lands. They are prepared by the Ministry of Agriculture, Forestry and Fisheries.

A 1:50,000 scale map series of soil types and productivity of cultivated lands has been prepared by the Agricultural Production Bureau since 1959, and the entire area of cultivated land, 51,000 km² in all, is covered.

A 1:20,000 or a 1:50,000 scale map series of soil types in national forests has been prepared by the Forestry Agency since 1947. 65,000 km² were covered by this series. This agency has also prepared a 1:50,000 scale map series of soil types for many private forests.

4.3 Geological Maps

The Geological Survey of Japan/ National Institute of Advanced Industrial Science and Technology (GSJ/AIST) has published most of geologic maps which cover the Japanese islands on scales of 1:50,000, 1:20,000, 1:1,000,000, 1:2,000,000 and 1:500,000.

A series of basic geologic maps published by GSJ/AIST is prepared on the scale of 1:50,000. This basic series was once prepared on the scale of 1:75,000 and the scale was changed to 1:50,000 in 1952. The coverage over the land becomes 914 sheets published out of 1274 (71.7%) at scale of 1:50,000 and 101 sheets published out of 124 (81.5%) at scale of 1:200,000. In addition, two thematic maps and seven digital geoscience maps (CD-ROM) were also published in 2003-2004. Compiling these basic geologic maps and other geologic information, GSJ/AIST published smaller scale maps. New gigital geoscience map series were also published as CD-ROMs, which include recent special thematic map digital publication titled "GeoHazard View" in 2004, in 2004, as well as "Geoscientific Maps of Southern Part of Korea, Western Part of Japan and Their Adjoining Seas 1:4,000,000 (CD-ROM Version)" jointly complied by GSJ and KIGAM (Korea Institute of Geoscience and Mineral Resources).

5. The National Atlas of Japan

The first edition of the National Atlas of Japan compiled by GSI was published in 1977. It has been widely acclaimed. GSI continued to revise this by using the latest statistics and other

source materials, and completed the National Atlas of Japan, Revised Edition, which was published in 1990. Furthermore, GSI has developed an Electronic Atlas System for the computer use, and a CD-ROM Atlas was published in 1997.

Now, GSI makes the base map data on the scale of 1:3,000,000 toward next generation atlas based on Web GIS.

6. National Land Surve y

The National Land Survey of Japan has been carried out under the direction and guidance of the National Land Agency (NLA) till 2000 and the Ministry of Land, Infrastructure and Transport (MLIT) since 2001. The objective of the survey is to contribute to the promotion of effective use and conservation of national land. To reveal the present condition of national land, such as land ownership and its utilization, is another objective of this survey. It is expected to be based on the National Land Survey Act which was enacted in 1951, when the survey was initiated. Three major items form the core of this survey; the land classification survey, the water use survey and cadastral survey.

6.1 Land classification Survey and Water Use Survey

A land classification survey is the survey of the topographical and geological features, soil, and present land use. The results are compiled into atlases and books. A water use survey aims at investigating the basic statistics of a river, such as annual rainfall, discharge, present water utilization for farming or drinking and groundwater.

In the land classification survey, NLA had developed a computerized mapping method in which a specific device, controlled by computer, can draw a colored map. By this method, one can easily identify various kinds of data related to land classification.

The above mentioned surveys are compiled into atlases and books as follows:

- a) Land classification maps (Geomorphological map, Surface geology map, Soil map, Present land use map, Land use capability classification map), overlays (such as slope map) and an Explanatory data book.
- b) Land conservation maps (Natural condition map, Present land use and vegetation map, Natural disasters map, Land use tendency and designated areas map, Control and designated area for disaster prevention map, Valuable natural and cultural assets distribution map, Basic conservation map) and Explanatory data book.
- c) Water use maps and a descriptive catalogue of available information on major river system.
- d) Groundwater maps and Explanatory data book.
- e) Groundwater data ledger.

	Scale	Coverage
Land classification map	1:200,000	All prefectures
	1:50,000 (c.m.m.)	All prefectures
	1:2,500 - 1:5,000 (c.m.m.)	152 cities
Land conservation map	1:200,000 (c.m.m.)	32 prefectures
	1:50,000	15 regions
Water use map	1:50,000	55 regions
	1:25,000 - 1:50,000	15 regions
Ground water map	1:15,000 - 1:50,000	11 regions

Table 8. Land Classification and Water Use Maps (1951-2004)

*c.m.m. : computerized mapping method

6.2 Cadastral Survey

The cadastral survey aims at clarifying the location, boundary, ownership, lot number, acreage, and current status of land use of each parcel. Local governments, such as prefectural and municipal governments, carry out the survey. They transact such affairs as planning the survey project, making contact with a surveying company, and supervising. MLIT plays a role in the survey by giving local governments a 50% subsidy of the total cost and some technical guidance as well. The executive body only has to share 1/20 to 1/30 of the total cost, since a special grant is given to the survey by the Japanese government. Because of present austere budget conditions, the progress of the survey has suffered a sharp curb. 1,500 km² or more is the acreage that the

cadastral survey has completed annually over the past five years. The progress of this survey at the end of FY2003 is as follows:

Completed cadastral survey: 1 30,837 km² (1951-2003)

Progress ratio: 45.7% (Target acreage of the survey: 286,200 km²)

The cadastral survey consists of the following stages; supplementary survey, detailed on-the-spot survey, measuring the acreage of each parcel, and making atlases and books. The supplementary survey comprises the control point survey which is to set up control points for cadastral surveying. The establishment of these control points is carried out by GSI. Scales of cadastral atlases differ from case to case depending on the mean acreage of a parcel. Scales of 1:250, 1:500, 1:1,000, 1:2,500, or 1:5,000 are used. Of these, the scales of 1:500 and 1:1,000 are the most commonly used. The required accuracy of measurement is classified into six types depending on the land use pattern. For a residential area, for example, the highest degree of accuracy is demanded. On the other hand, the accuracy level for a forest area is the lowest.

Copies of cadastral maps and books are bound to be sent to registry offices after having been checked for accuracy and obtaining the legal approval of MLIT, or, in some cases, from the prefectural governor, to replace the old maps which were prepared about 100 years ago and are still used for levy and land registration.

The cadastral survey had not been promoted well, and in an attempt to do so, the acceleration Act, named The Act on Sp ecial Measures for Promotion of the National Land Survey was enacted in 1962. Under this Act, target acreage for the survey for a period of 10 years was clearly established. Now the survey has been being carried out based on its fifth, the Ten-year National Land Survey Plan stage (2000-2009). According to the Plan, the target acreage is 34,000 km².

7. Marine Geology

GSJ/AIST has been engaged in marine geological and geophysical investigation of the sea around the Japanese Islands, the western and central Pacific Ocean and the Antarctic sea, chartering the geological survey vessel R/V Hakurei-maru, R/V Hakurei-maru II, and others. The investigation comprises basic studies of marine geology, mineral resources and geophysical prospecting, including sedimentological and environmental study of lacustrine and coastal areas. Marine geological maps on the scale of 1: 1,000,000 covering the Japanese islands were published and a series of marine geological maps on the scale of 1: 200,000 has been published around the main Japanese Islands. Since 2002, marine geological maps on the scale of 1: 200,000 has been published around the main Japanese Islands. International cooperation is actively promoted in the fields of marine geology, mineral resources and environmental study of coastal areas.

8. Hydrographic Work

8.1 Hydrographic Surveying and Charting

The datum of Japanese nautical charts were converted from the Tokyo Datum (TD) into the World Geodetic System (WGS) during the period from April 2000 to March 2002. a) The number of various hydrographic surveys carried out are as follows:

	-				
Type of survey	2000	2001	2002	2003	2004
Harbor	1	2	3	1	1
Updating	195	194	210	231	210
Coastal	14	11	9	9	9
Basic Maps of the Sea	5	5	1	0	0
Earthquakeprediction	7	9	11	13	12

Table 9. Hydrographic Surveys

b) The results of these surveys were used for production of nautical and other charts, as shown in Table 10:

Table 10. Nautical and Other Charts

Т	ype of chart	2000	2001	2002	2003	2004
New Charts	Nautical charts	189	421	2	15	36

	Miscellaneous charts	1	0	1	0	7
	Basic Maps of the Sea	5	15	11	0	0
	Aeronautical charts	0	0	0	0	0
New Editions	Nautical charts	2	9	110	100	97
	Miscellaneous charts	0	4	2	0	3
	Basic Maps of the Sea	0	0	0	1	0
	Aeronautical charts	0	0	0	4	6
Reprints		0	0	13	1	1
Total		197	449	139	121	150

Note: The charts whose datum were converted into WGS-84 are included in Nautical charts of New Charts.

The Basic Maps of the Sea (BMS) currently produced are classified as follows:

Series Scale		Coverage	Size	Туре
BMS in Coastal	1:10,000	Within 12M	Full	Bathymetry; Submarine structure
Waters	1:50,000	of the coast	1/2	
BMS on Continental	Mainly	Continental	Full	Bathymetry; Submarine structure; Total
Shelf Areas	1:200,000	margin		magnetic intensity; Gravity anomaly
BMS in Ocean	1:3,000,000	Ocean Area	Full	do. (except Submarine structure;)
Areas				

c) The number of paper charts issued as of March 2005 is shown below:

	Table 12.	Number	of Pape	er Charts	Issued	
--	-----------	--------	---------	-----------	--------	--

Type of Chart	Number of Issues
Nautical charts	749
Miscellaneous charts	95
Basic Maps of The Sea	494
Aeronautical charts	25
Total	1.363

Note: The International Charts of the IHO under the responsibility of Japan as the produce nation, i.e. six of the 1:3,500,000 series and two of the 1:10,000,000 series have been published.

d) Electronic Navigational Charts (ENCs)

Table 13. Number of ENCs Issued as of April 2005

Type of Chart	Number of Issues
Electronic Navigational Charts	495 cell

8.2 Other Publication Activities

Table 14. Other Publications of HOD

Type of publication		2000	2001	2002	2003	2004	
New	Sailing	(Japanese)	1	1	1	1	1
publications	Directions	(English)	1	3	2	2	1
	Special public	ations	6	6	6	5	5
New Editions	Sailing	(Japanese)	6	5	5	5	5
	Directions	(English)	0	1	2	3	4
	Special public	ations	3	7	3	5	3
Notices to	(Japanese)		4,965	5,524	6,065	4,855	3,809
Mariners	(English)		4,533	5,194	5,543	4,544	3,629
Japan Navigational Warnings (Japanese)		2,403	2,656	2,682	2,786	2,612	
NAVAREA XI navigational warnings (English)		799	947	950	653	600	
NAVTEX navigation warnings (Japanese)		2,030	2,180	2,095	2,335	2,136	
NAVTEX navigational warnings (English)			2,030	2,180	2,095	2,335	2,136
Information of	Quick Bulletin	of Ocean Condition	24	50	51	51	50

Ocean	Ocean Current Foreca sting	50	51	51	51	51
Conditions	-					

8.3 Marine Survey

a) Survey of coastal Area

In order to cope with the establishment of 200-mile exclusive economic zone (EEZ) in accordance with the United Nations Convention on the Law of the Sea (UNCLOS), HOD is carrying out detailed surveys of low-water lines, topography and geological structure of the sea-bed in coastal area, particularly in those important areas around baseline defining the Japanese territorial sea. Japan concluded UNCLOS in 1996.

b) Airborne Laser Hydrography

HOD and 6th Regional Japan Coast Guard Headquarters (RJCGH) has been carrying out airborne laser hydrography operations science 2004 for the mapping of the mapping of very shallow waters. In 2004, HOD and 6th RJCGH surveyed the Island sea, Setonaikai.

c) Survey of Continental Shelf Areas

HOD is carrying out hydrographic surveys south of Japan by using the large-type survey vessel "TAKUYO and SHOYO" equipped with modern survey instruments such as multi-beam echo sounder in order to obtain basic data required for the promotion of utilization and development of the continental shelf of Japan.

d) Promotion of Marine Geodetic Survey

Nautical charts of each country are constructed based on its own geodetic system. With the recent development of the geodetic satellite survey technique, however, a difference in geodetic systems has turned out to be a problem. Accordingly, the IHO recommends that the meridians and parallels given on the chart should be shown on the basis of the World Geodetic System. Therefore, in Japan also, it becomes necessary to locate the mainland and remote islands on the basis of the World Geodetic System, and HOD has been conducting geodetic satellite observations by laser ranging to the geodetic satellite LAGEOS, in cooperation with the United States National Aeronautics and Space Administration (NASA) to obtain the precise location of the mainland on the basis of the World Geodetic System.

e) Surveys Earthquake Prediction Program

HOD surveys for the earthquake prediction program. In order to obtain data information necessary for the prediction of earthquake, HOD has been carrying out surveys and investigations for submarine topography and/or active sea-bottom structures at specific areas off Miyagi, near Nankai trough, off Takachi and Tokachi off Shimane.

8.4 Provision and Supply of Oceanographic Data and Information

HOD has been engaged in collecting, managing and supplying oceanographic data and information for 40 years as a comprehensive oceanographic data bank established in accordance with a resolution adopted by the Intergovernmental Oceanographic Commission (IOC) of UNESCO and a report made by the Council for Ocean Development of Japan. The Oceanographic Data and Information Division of HOD is registered as the National Oceanographic Data Center of Japan (Japan Oceanographic Data Center: JODC) under the framework of International Oceanographic Data and Information Exchange (IODE) promoted by the IOC, and is taking active part in internationally exchanging oceanographic data and information for their effective utilization as the Japanese representative in the field of oceanographic data exchange.

JODC provides service of on-line data access by J-DOSS (JODC Data On-line Service System). JDOSS is a system for retrieving and providing oceanographic data and information managed by JODC through the Internet.

9. GIS Activities

9.1 GIS Action Program 2002-2005

The Liaison Committee of Ministries and Agencies Concerned with Geographic Information System has continued its efforts for infrastructure development after the end of the Long-term Plan for the Development of NSDI in Japan, acknowledging once again the importance of promoting efficient and high-quality activities based on GIS in various fields from administration, industrial development to the every-day life of the people. Also GIS has come to be recognized as an indispensable tool for implementing IT related policies including the "e-Japan Strategy" the government endorses, as well as for creation of new business models and an improved quality of life of the people by an intelligent administration and better public services. The role of GIS is expected to gain further momentum in the years to come.

To meet the growing national needs for GIS and to ensure continuous efforts on GIS, the government formulated a new plan "GIS Action Program 2002-2005" in February 2002, for the period of 2002-2005. (The program was revised on April 2003 and on April 2004 for additional measures and some amendments.) This Action Program aiming at an easier and a better utilization of GIS data envisions an IT society where the following are highlighted:

- efficiency, greater speed, better quality of the public services
- creation of new business models in the industrial sector and new employment
- provision of better services in the overall public services at a minimum cost

The latest program includes about 70 specific actions to be taken, which can be summarized as follows:

- 1). Promotion of standardization concerning national spatial data Infrastructure and promotion of improved administrative efficiency through governmental lead in using GIS
- 2). Development of systems and guidelines from the perspective of promoting digitization and distribution of the geographic information
- 3). Promotion of digitization and provision of geographic information
- 4). Support for full-scale propagation of GIS

5) Realization of efficient administration and high-quality administrative services using GIS

9.2 Digital Japan

Digital Japan is a concept of a virtual space where users can utilize geographical information selecting from data sets stored and maintained by different organizations in the internet and integrating them for certain purpose based on the positional reference data. Digital Japan has various possibilities that enable us to search and analyze geographical information as an infrastructure, as well as to add information to them on demand of users.

In administration for example, Digital Japan may offer the essential information for daily life using maps in easy manner as follows: reflection of residents' opinion, dialogues with the residents, promotion of local activities and dissemination of disaster measures based on the latest geographical information.

GSI believes that Digital Japan can be applied to as great many fields as combinations of the value-added information and data infrastructure.

To realize Digital Japan, GSI will launch Digital Japan Web System in 2003, which enables us to overlap many kinds of geographical information on the data developed by GSI and some local governments on the Internet.

GSI will continuously maintain geographical information infrastructure that is indispensable for Digital Japan and also for common use by citizens while actively develops procedures to make a smooth maintenance and distribution of positional reference data and geographical information possible.

10. International Activities

10.1 International Geodetic Survey

GSI is actively participating in international cooperative projects in the field of geodesy, such as IGS (International GNSS Service), DOSE (Dynamics of Solid Earth) and IAGBN (International Absolute Gravity Basestation Network), in order to determine precise positions in global coordinate system and to contribute to the progress of geodesy and earth sciences. The IGS provides precise orbits of the GPS satellites. It is one of the most important information for precise GPS observation. GSI participates in the IGS as one of the Operational Data Centers and the Regional Network Associate Analysis Centers.

IVS is an international collaboration of organizations which operate or support VLBI and GSI participates in it through intercontinental joint VLBI observation. GSI also participates in the international research of JAXA on Japanese Earth Resources Satellite-interferometric SAR.

GSI, cooperating with Kyoto University, has been conducting absolute gravity measurements in east Asia since 2003, in order to establish an absolute gravity network as a reference for gravity study in the region.

The measurements were done in China, Malaysia and Indonesia.

10.2 Global Mapping Project

Global Mapping is a cooperative project of NMOs and partners to develop a set of global geographic data with known and verified quality based on consistent specifications. As of March 2005, 141 countries and regions have participated in the project, and twenty countries' data have been completed and are downloadable through the Internet from the ISCGM website. The project has been promoted through International Steering Committee for Global mapping (ISCGM) established in 1996.

The need of the Global Map for addressing global environmental problems has been well confirmed at the United Nations. The Plan of Implementation adopted at the World Summit on Sustainable Development (WSSD) emphasizes the necessity for promoting development and wider use of earth observation technologies, including global mapping and calls for encouraging initiatives and partnerships for global mapping. Also, Global Mapping became a registered WSSD Type 2 initiative (a sustainable development initiative with an emphasis of partnership aspects) with the goal of completion of global coverage by the year 2007. Additionally, importance of development of global geographic framework is also recognized at the Earth Observation Summit and ISCGM is involved in drafting the Global Earth Observation System of Systems (GEOSS)'10-Year Implementation Plan Reference Document.

GSI is developing not only the Global Map of Japan but also the Global Map of developing countries mainly in Asia and the Pacific region in cooperation with respective NMOs. To date, data of the following countries have been developed: Thailand, the Philippines, Vietnam and Kazakhstan in 1998; Mongolia Kyrgyz and Bangladesh in 1999; Laos and Nepal in 2000; Myanmar and Sudan in 2001; and Senegal and Liberia in 2002; and Congo, Swaziland and Honduras in 2003. GSI will continue to make efforts to implement Global Mapping Project as ISCGM Secretariat.

10.3 ISO/TC211 (Geographic information/Geomatics)

GSI has actively participate d in ISO/TC211 since the foundation in view of the magnitude of standardization of geographical information and promotes it developing Japanese Standards for Geographic Information (JSGI) in accordance with ISO/TC211.

GSI published JSGI2.0 in March 2002 in accordance with the international standards. The JSGI2.0 is based on JSGI published in 1999 and reflects examinations of practical concerns for the implementation in Japan through a joint research with 38 private enterprises titled "Study for practical Standards for Geographic Information."

"GIS Action Program 2002 – 2005" states that Japanese government takes the initiative to utilize JSGI at maintenance, dissemination of data and other occasions, and to promote implementation of JSGI and provide technical assistance.

10.4 International Hydrographic Organization (IHO)

IHO Commissions, Committees and Working Groups in which Japan (HOD) has been participating are as follows:

a) Finance Committee (FC)

b) IHO Commission on Promulgation of Radio Navigational Warnings (CPRNW)

c) IHO Worldwide Electronic Navigational Chart Data Base Committee (WEND)

d) IHO Committee on Hydrographic Requirements for Information Systems (CHRIS)

e) CHRIS Data Quality Working Group (DQWG)

f) CHRIS Transfer Standard Maintenance and Application Development Working Group (TSMAD)

g) CHRIS Standardization of Nautical Publications Working Group (SNPWG)

h) IHO Chart Standardization and Paper Chart Working Group (CSPCWG)

i) IHO/IEC Harmonization Group on MIO (HGMIO)

j) IHO-IAG-IOC Advisory Board on the Law of the Sea (ABLOS)

k) Joint IHO-IOC Guiding Committee for the General Bathymetric Chart of the Oceans (GEBCO)

I) GEBCO Sub -Committee on Digital Bathymetry (SCDB)

m) GEBCO Sub-Committee on Undersea Feature Names (SCUFN)

- n) IHO Working Group on Standards for Hydrographic Survey S-44
- o) IHO Tidal Committee (TC)
- p) IHO Hydrographic Committee on Antarctica (HCA)
- q) IHO Strategic Planning Working Group (SPWG)
- r) East Asia Hydrographiic Commission (EAHC)

10.5 Intergovernmental Oceanographic Commission (IOC)

HOD has also been working as a member of IOC which is the subsidiary body of UNASCO and has been participating in international joint projects are as follows:

- a) International Oceanographic Data and information Exchange (IODE) National Coordinator
- b) IODE Regional Coordinator for WESTPAC
- c) International Bathymetric Chart of Western Pacific (IBCWP)
- d) North East Asian Regional GOOS (Global Ocean Observing System)/Co-ordinating Committee (NEAR-GOOS)
- e) Intergovernmental Working Group on IOC Oceanographic Data Exchange Policy

10.6 United Nations Environment Programme (UNEP)

HOD has also been working as a member of NOWPAP (Northwest Pacific Action Plan) which is the subsidiary body of UNEP and has been participating are as follows:

- a) NOWPAP Data and Information Network/Regional Activity Center (DINRAC) Focal Point (NOWPAP/1)
- b) NOWPAP Marine Environmental Emergency Preparedness and Response/Regional Activity Center (MERRAC) Specific Projects; Expert on Oil Spill Prediction Model (NOWPAP/4)
- c) NOWPAP MERRAC Specific Projects; Expert on Sensitivity Mapping (NOWPAP/4)

10.7 International Lunar Occultation Centre

HOD conducts astronomical observation under international cooperation and makes efforts to improve the accuracy of ephemeris. Particularly from April 1981, upon the request of the International Astronomical Union (IAU), HOD took over the activities performed by the Royal Greenwich Observatory as the International Lunar Occultation Centre and started to collect and analyze observations all over the world in a homogeneous manner.